



- NOTES:
- 1) CORDAGE: 18/3, SJOW, 90°C, BLACK
  - 2) APPROVALS: (UL) (ETL)
  - 3) RATING: 10 AMP/125 VOLTS
  - 4) FLAME RATING : FT2
  - 5) CORDAGE D.D. : .350 (REF.)
  - 6) PACKAGING: 25 BAGGED CORDS PER CARTON
  - 7) ALL DIMENSIONS IN inches.

VOLEX RESERVES THE RIGHT TO ALTER NON-CRITICAL DIMENSIONS WITHOUT NOTICE.

**Volex**  
**CUD**

FORM IN71-07 REV.A

Indianapolis, IN  
 Conover, N.C.  
 Freemont, CA  
 Aguascalientes, MX  
 Tijuana, Mexico  
 Hermosillo, MX  
 Clinton, AR  
 Kanata, Canada

**Proprietary Notice:**  
 This document is the property of Volex Incorporated. The information contained herein is not to be disclosed to anyone without the express written consent of Volex Inc.

**MATERIAL:**  
 PLUG: PVC, BLACK  
 JACKET: PVC, BLACK  
 RDS COMPLIANT

**FINISH:**  
 JACKET: SMOOTH

SCALE:	ECD:	ITEM DESCRIPTION																								
NDT TO SCALE	N/A	RETRACTILE - NORTH AMERICAN POWER SUPPLY CORD (1')																								
REV	DESCRIPTION	DATE																								
1	C.U.D - NEW RELEASE	9/10/07																								
<table border="1"> <tr> <td>TOLERANCE SPECIFIED</td> <td>APPROVED</td> <td>DRAWN BY</td> <td>DATE:</td> </tr> <tr> <td>.XXX ± .005</td> <td>STC</td> <td>STC</td> <td>9/10/07</td> </tr> <tr> <td>.XX ± .02</td> <td></td> <td></td> <td></td> </tr> <tr> <td>.X ± .03</td> <td></td> <td></td> <td></td> </tr> <tr> <td>FRACT. ± 1/32°</td> <td></td> <td></td> <td></td> </tr> <tr> <td>ANGULAR ± 1/2°</td> <td></td> <td></td> <td></td> </tr> </table>			TOLERANCE SPECIFIED	APPROVED	DRAWN BY	DATE:	.XXX ± .005	STC	STC	9/10/07	.XX ± .02				.X ± .03				FRACT. ± 1/32°				ANGULAR ± 1/2°			
TOLERANCE SPECIFIED	APPROVED	DRAWN BY	DATE:																							
.XXX ± .005	STC	STC	9/10/07																							
.XX ± .02																										
.X ± .03																										
FRACT. ± 1/32°																										
ANGULAR ± 1/2°																										
PART NO.		17447 10 S2																								