



Part Number: ST-SOLDER-ST1
Description: Fixture Free Solder Machine
18167-TL

3608



- Power Supply: 115 VAC
- Maximal Power: 75 W
- Temperature Range : 350 °F ~ 895°F / 175 °C ~ 480°C
- Length of Power Cord: 79 Inches / 2 Meters
- Temperature Stability: ± 9 °F / ± 5 °C
- Length of the Foot Pedal's Wire: 79 Inches / 2 Meters
- Motor Output: DC 12V , 3.42 W
- Fan/Activated Carbon Filter. Output: 4.5 W
- Solder Feed Time: 0 ~1 Second
- Solder Feed Speed: 0 ~ 4 Inches (0 ~ 100mm) / Second
- Controlling Mode: Pulse and Continuous (Selectable)
- Usable Solder Dia.: 0.024 ~ 0.063 Inches / 0.6 ~ 1.6 mm
- Retract Feed Speed: 0 ~ 4 Inches (0 ~ 100mm) / Second
- Exterior Dimension(L x W x H): 14.5 x6.4 x 12.9 (Inches)
368 x 163 x 327(mm)
- Weight (Net): 6.8 Lbs. / 3.1 Kg
- Vertical Swing Adjustment: 15 ° up and 45 ° down
- Height Adjustment: 7" to 10" while the unit's vertical range is at 90 ° from the base of the unit
- Horizontal Swing Adjustment: 54 ° from 0 ° position (total of 108 °)
- RoHS Compliant
- CE Approved



MARLIN P. JONES & ASSOC., INC.

P.O. Box 530400 Lake Park, Fl 33403
800-652-6733 FAX 561-844-8764
WWW.MPJA.COM