

IBQ101/IBQ102

Hand-Held
Frequency Counter
Users Manual

手持式频率计 用户手册

CONTENTS

1. Introduction	10
2. Features	10
3. Use	10
(1) Key Functions	10
(2) Turning on and Turning off Power	11
(3) Turning on Back Light	11
(4) Holding Display	11
(5) Setting up Menu	12
(6) Setting up Measure Range	12
(7) Setting up Gate	12
(8) Setting up User Menu	13
1) Setting up Display Hold	13
2) Setting up Save	13
3) Viewing Saved Data	14
4) Selecting Filter	14
5) Selecting Automatic Power Off	14
(9) Signal Strength Indicator	14
4. Maintenance	15
(1) Keeping the frequency counter	15
(2) Charging the battery	15
(3) Extending the battery operating hours	16
(4) Calibration	16
5. Warranty and service	16
6. Specifications	17

— 8 —

IBQ101/IBQ102

Congratulations on your purchase of **IBQ101**

(2) Hand-Held Frequency Counter. Before Operating the frequency counter, please read this manual thoroughly.

Make sure that the following accessories are supplied with your frequency counter:

Antenna (1)
AC Power Adapter (1)

Please contact the sales agent in case of accessory missing.

IBQ101/IBQ102

1. Introduction

Easy to operate, reliable in quality, and small in size, **IBQ101(2)** hand-held frequency counter is a super compact frequency measuring instrument.

2. Features

Multi-Function LCD Display
9-Digit Display
Analog bar and Digit Signal Strength Indicator
Display Holding
50 Display Readings Saving
Power Indicator
Interactive User Menu
Equipped with UV antenna and USB power adapter.

3. Use

(1) Key Functions

When power is turned on, the lower part of screen indicates the present function of the 3 keys

[LIGHT] : Function used to turn on or turn off the back light. No key operation for 5 minutes, the back light turns off automatically to save power.

[MENU] : Function used to enter the menu

[HOLD] : Function used to hold the screen

reading

[EXIT]: Function used to exit the menu

[SEL]: Function to confirm the selection and return to the previous menu

[NEXT]: Function used to select next

[BACK]: Function used to return to the previous menu.

(2) Turning on and Turning off Power

Hold [F1] key for two seconds and the logo appears on the screen. The frequency counter now works.

Hold [F2] key for 2 seconds to turn off the frequency counter. **POWER OFF!** appears on the screen.

(3) Turning on Back Light

Press [F1] key to turn on the back light. Press [F1] key again to turn off the back light. No key operation for 5 minutes, the back light turns off automatically to save power.

(4) Holding Display

Press [F3] key to hold the frequency and signal strength reading on the screen. **HOLD** indicator is indicated on the screen. Press [F3] again to turn off display holding, and **HOLD** indicator disappears. In Display Holding mode, the function of [F2] (MENU) is **SAVE**. The frequency

and signal strength readings can be saved sequentially by pressing [F2]. **SAVE** indicator flashes on the screen when saving. After saving, **SAVE** indicator disappears. [F2] is restored to the function of MENU, and display holding is turned off.

(5) Setting up Menu

Press [F2] key to enter the menu.

There are 3 options in the menu:

[Range]: Measure range,

[Gate]: Gate setup

[User]: User menu setup

Press [F1] key to select the option.

Press [F2] key to enter the sub-menu.

Press [F3] key to exit the menu.

(6) Setting up Measure Range (Only IBQ102)

Select Range in the menu.

Press [F3] key to select measure range.

Input Impedance is 50 ohms when 50MHz - 2.6GHz range is selected.

Input impedance is 1 Meg ohms when 10Hz - 100MHz range is selected.

(7) Setting up Gate

Select Gate in the menu.

Press [F2] to enter GATE options. Press [F3]

to select the appropriate gate time. Press [F1] to exit.

(8) Setting up User Menu

Hold: Function to hold the reading

Save: Function to save the measured data

View: Function to view the saved data

Filter: Function to filter the unwanted signal so as to display "0" when the frequency counter is not measuring any signals.

Auto off: Function to turn off the power Automatically. The frequency counter is turned off 5 minutes after it is turned on, if ON is selected.

1) Setting up Hold

Select Hold in User Menu. Press [F3] key to select Auto or Manual. When Auto is selected, press [F2] key to enter the holding level preset menu. Press [F2] key to increase the level, or press [F3] to decrease the level. When Manual is selected, holding level is set manually. Press [F1] key or [F2] key to return to the previous menu.

2) Setting up Save

Select Save in the User Menu. If Auto is selected, data is saved automatically; if Manual is selected, data is saved manually.

Set Hold to Auto to start automatic saving. When the strength of the measured frequency

exceeds the automatic holding level, the measured frequency and signal strength are saved. **SAVE** indicator flashes in the saving process. **SAVE** indicator disappears after saving.

In case of manual saving, press [F3] key to hold the screen reading. [F2] key now works as **SAVE**. Press [F2] key to save the reading. **SAVE** indicator flashes in the saving process. **SAVE** indicator disappears after saving.

3) Viewing Saved Data

Select View in the User Menu to display the saved frequency and signal strength. The right lower corner indicates the location of the saved data in the memory. Press [F2] key or [F3] key to view the data. Press [F1] key to return to the previous menu.

4) Selecting Filter

Select Filter in the User Menu. ON or OFF can be selected. The default selection is ON.

5) Automatic Power Off

Select Auto Off in the User Menu. Select ON to start automatic power off. Select OFF to disable automatic power off.

(9) Signal Strength Indicator

Analog bars and digits are both used to indicate the measured frequency signal strength.

The resolution of the indicator is 1dB. The maximum input sensitivity is -40dBm, input ranging from -40dBm~-15dBm. The signal strength is only for reference, if the antenna is used to pick up the frequency to be measured.

4. Maintenance

(1) Keeping the frequency counter

If the frequency counter is not to be used for an extended period, please remove the battery. Open the battery cabin cover to remove the battery.

(2) Charging the battery

When the frequency counter is used for the first time, the power of the removable battery in the frequency counter may be not enough. Please charge the battery before use. With the USB power adapter, the battery can be charged. The frequency counter does not have the function of exchanging data with the computer. Do not connect this USB to the PC USB.

When the adaptor is connected, the LED at the upper right corner lights, indicating battery charging. When charging is finished, the green LED lights. The battery is also charged when the frequency counter is in use.

The battery indicator at the upper right corner indicates the battery condition. When low

battery indicator appears, please charge or replace the battery as soon as possible.

(3) Extending the battery operating hours

The frequency counter can be turned off automatically to save power if auto-power-off is turned on. If no key is pressed in 5 minutes, the frequency counter is turned off automatically. Three AAA Ni-MH batteries are used in the frequency counter. The built-in charging circuit manages the Ni-MH battery charging effectively. Heavy duty alkaline batteries can also be used to power the frequency counter. But never try to charge the alkaline batteries.

(4) Calibration

Connect the frequency counter to a standard frequency source. Remove the battery from the frequency counter and use power adapter to power the frequency counter. Adjust the CAL variable capacitor, until the frequency reading is the same with the standard signal.

5. Warranty and Service

The warranty time is one year. The damage caused by any of the following is not covered under the warranty: Damage caused by using the ordinary battery, damage caused by improper use, damage caused by revising, and damage caused by accidents.

6. Specifications

Model	IBQ101		IBQ102	
Range	50MHz-2.6GHz		10Hz-100MHz	50MHz-2.6GHz
Amplifier	50 ohm		1 Meg ohm	50 ohm
Impedance	50 ohm		1 Meg ohm	50 ohm
	VSWR<2:1		30pF	VSWR<2:1
Features	RF signal strength		RF signal strength(50MHz-2.6GHz)	
	Screen Holding		Screen Holding	
	Save		Save	
	View		View	
	Battery Indicator		Battery Indicator	
Sensitivity	<5mV@100MHz		<30mV@10Hz-	<5mV@100MHz
	<5mV@400MHz		50MHz	<5mV@400MHz
	<15mV@1GHz		<35mV@50MHz-	<15mV@1GHz
			100MHz	
Gate	0.1ms		0.01 s	0.1ms
	0.1s		0.1 s	0.1s
	1s		1 s	1s
Time Base	<+/-30ppm		<+/-5ppm	
LSD	100Hz/1s		1Hz /1s (10Hz-100MHz)	
			100Hz /1s (50MHz-2.6GHz)	
Battery	3 X AAA Ni-MH			
Power	5VDC 1A			
Cabinet	ABS			
Size	85mm (H)55mm(D)24mm(W)			
ANT	(UHF)			

IBQ101/IBQ102

Hand-Held
Frequency Counter
Users Manual

手持式频率计 用户手册