


Item # W199AX-8, 199 Open Style Power Relays / DPST-NO, 40 Amp Rating (AC)



[larger image](#)



[larger image](#)

[Contact Characteristics](#) · [Specifications](#) · [Coil Characteristics](#) · [Performance Characteristics](#) · [Environment](#) · [Product Certifications](#)

**Contact Characteristics**

Contact Rating	40 A
Contact Configuration	DPST-NO
Contact Materials	Silver Alloy
Maximum Switching Voltage	600 V
Switching Current at Voltage (AC, Resistive)	40 A at 277 V 50 / 60 Hz
Switching Current at Voltage (DC, Resistive)	40 A at 28 VDC
Switching Current at Voltage (Pilot Duty)	A600
Minimum Switching Requirement	1 A at 12 VAC

**Specifications**

Nominal Input Voltage	24 VAC 50/60 Hz
Coil Resistance	12 Ohm
Cover Style	Open Style
Weight	227 to 312 G

**Coil Characteristics**

Operating Range - % of Nominal (AC)	85 to 110 %
Operating Range - % of Nominal (DC)	80 to 110 %
Average Consumption (AC)	10 VA
Average Consumption (DC)	4 W
Drop-out Voltage Threshold (DC)	10 %
Drop-out Voltage Threshold (AC)	10 %

**Performance Characteristics**

Electrical Life (UL508), Operations at Rated Current (Resistive) ?	100000
Mechanical Life, Unpowered ?	1000000
Operating Time (Response Time)	30 ms

**Environment**

Ambient Air Temperature around the Device - Storage	-40 to +85 °C
Ambient Air Temperature around the Device - Operation	-40 to +55 °C
Connection	8 AWG 10 mm <sup>2</sup>
Terminal Tightening Torque	7 to 9 in lb 0.8 to 1.0 N·m

**Product Certifications**

<b>Agency Approvals</b>	UL CE CSA RoHS
-------------------------	-------------------------

---

[Print](#) [Back](#)

---